

b.safe



NEW

b.safe HPLC Waste Collector Justrite®
M 815-01, M 817-01,
M 825-01, M 827-01

Technical Details

b.safe HPLC Waste Collector Justrite made of PE-black

Collection of **HPLC waste in Justrite® containers**, connections compatible with the standard quick couplings made of polypropylene or stainless steel.

b.safe Exhaust Filter Adapter Justrite made of PE-black

Adaptor made of **PE-black** for use of b.safe Exhaust Filters for safe collection of **HPLC waste in Justrite® safety containers** without escape of harmful solvent vapors.

C
M 815-01

A
M 825-01

b.safe Exhaust Filter Adapter Justrite made of PE

Adaptor made of **EX** for use of b.safe Exhaust Filters for safe collection of HPLC waste in Justrite® safety containers without escape of harmful solvent vapors.

D
M 817-01

B
M 827-01

HPLC Waste Collector Justrite made of PE

Collection of **HPLC waste in Justrite® containers**, connections compatible with the standard quick couplings made of polypropylene or stainless steel.



b.safe HPLC Waste Collector Justrite®

Material: **PE-EX, PE** | Temperature resistance: **0 °C to +80 °C** | Chemical resistance: **++ very good**

Collector for assembly on the lateral couplings of Justrite® Disposal Safety Cans for collection of HPLC waste, six connections for capillaries with O. D. 1,6/2,2/3,2 mm (thread UNF 1/4") and seven hose connectors for tubing I. D. 5,5-8 mm (Gewinde NPT 1/8"). Fittings for capillaries, hose connectors and blind fittings to close

unused connections are included. Version either with collector and coupling made of polypropylen or with collector made in static dissipative PE-EX.

Application: For collection of HPLC waste in Justrite® Disposal Safety Cans. Compatible with the standard quick-disconnect couplings in polypropylene and stainless-steel.

	Material Adaptor	Material Coupling	Number of Blind Fittings	Number of Blind Blindfittings	Hose Connectors	Cat.No.:
A	PE-EX	Stainless Steel	6 x Ø 1,6 mm (green) 6 x Ø 2,2 mm (purple) 6 x Ø 3,2 mm (yellow)	6 x milky white (UNF) 7 x white (NPT)	2 x 5,5 – 8 mm	M 825-01
B	PP	PP	6 x Ø 1,6 mm (green) 6 x Ø 2,2 mm (purple) 6 x Ø 3,2 mm (yellow)	6 x milky white (UNF) 7 x white (NPT)	2 x 5,5 – 8 mm	M 827-01



b.safe Exhaust Filter Adapter Justrite®

Material: **PTFE, PE** | Temperature resistance: **0 °C to +80 °C** | Chemical resistance: **++ very good**

Adaptor for assembly on the lateral couplings of Justrite® Disposal Safety Cans, with connector to screw in a b.safe Exhaust Filter (thread GL14) for venting the disposal can during filling. Version either in PP-grey for a PP-coupling or in PE-black for a stainless steel coupling.

Application: Adaptor for the use of b.safe Exhaust Filters on Justrite® Disposal Safety Cans in order to restrain solvent vapours from the escaping air during filling with HPLC waste.

	Material Adaptor	Material Coupling	Cat.No.:
C	PE-black	Stainless Steel	M 815-01
D	PP	PP	M 817-01



Optimal extension: Justite® with level monitoring

b.safe Disk Sensor

The disk sensor reliably ensures level control. Simply fix it on the outside of the container at the desired height level - when the level is reached, a message is sent to the Mini-Display-Table.

Description	Cat. No.
A b.safe Exhaust Filter	M 506-01, -02, -03
B b.safe Exhaust Filter Adapter Justrite	M 815-01, M 817-01
C b.safe Disk Sensor	R 640-05
D b.safe Signal Cabels	R 645-02
E b.safe Mini-Display Table	R 659-01
F b.safe HPLC Waste Collector Justrite	M 825-01, M 827-01

b.safe Mini-Display Table

If the Mini-Display Table receives the message that the fill level has been reached, it emits a signal tone.

Request a free b.safe catalog now!

Discover our complete product range, valuable tips for enhanced safety in the HPLC laboratory, and practical assistance in selecting the right solutions for your requirements.

Scan the QR code and request
the catalog now or at:
www.bsafede/catalogue-request

